

Stäbe

extrudiert, geschliffen

Durchmesser mm	Gewicht kg / m	T o l e r a n z e n			
		Durchmesser mm	Längen mm		
3,0	0,015	+ 0 / - 0,05	+ 20 / - 0		
4,0	0,026				
5,0	0,050				
5,5	0,058				
6,0	0,060				
6,5	0,070				
7,0	0,081				
7,5	0,084				
8,0	0,107				
9,0	0,135				
10,0	0,167				
11,0	0,202				
12,0	0,240				
13,0	0,282				
14,0	0,327				
15,0	0,376				
16,0	0,428	+ 0 / - 0,08			
17,0	0,483				
18,0	0,542				
19,0	0,603				
20,0	0,700				
21,0	0,800				
22,0	0,809				
23,0	0,885				
24,0	0,963				
25,0	1,045				
27,0	1,219	+ 0 / - 0,1			
28,0	1,311				
30,0	1,505				
32,0	1,713				
33,0	1,821				
34,0	1,933				
35,0	2,049				
38,0	2,415				
40,0	2,676				
50,0	4,330				
60,0	6,230	+ 0 / - 0,2			

Standard-Längen:

Durchmesser: 3 - 10 mm : 2000 mm
3000 mm
über 10 mm: 2000 mm

Gewichte: ungefähre Gewichte der
Effektivabmessungen

Zwischenabmessungen sind fertigungstechnisch
möglich (auf Anfrage)