

Rohre extrudiert

Durchmesser			Durchmesser			
D	d	Gewicht	D	d	Gewicht	
mm	mm	kg / m	mm	mm	kg / m	
10,0	4,0	0,165	27,0	10,0	1,234	
	5,0	0,155		12,0	1,166	
	6,0	0,135		15,0	1,040	
	7,0	0,115		18,0	0,883	
				20,0	0,761	
12,0	5,0	0,230		24,0	0,486	
	6,0	0,215		30,0	6,0	1,632
	8,0	0,170			8,0	1,591
14,0	6,0	0,303			10,0	1,537
	8,0	0,310			12,0	1,470
	10,0	0,210	14,0		1,389	
15,0	6,0	0,354	15,0		1,343	
	8,0	0,310	18,0		1,186	
	10,0	0,255	20,0		1,065	
16,0	5,0	0,429	22,0		0,930	
	6,0	0,408	33,0		20,0	1,400
	8,0	0,364		25,0	1,037	
	10,0	0,307		29,0	0,686	
	12,0	0,236		35,0	10,0	2,111
18,0	5,0	0,548			12,0	2,044
	6,0	0,526	16,0		1,868	
	8,0	0,482	18,0		1,760	
	10,0	0,425	20,0		1,639	
	12,0	0,354	22,0	1,504		
20,0	5,0	0,678	25,0	1,276		
	8,0	0,614	28,0	1,020		
	10,0	0,556	40,0	10,0	2,840	
	12,0	0,486		12,0	2,766	
	14,0	0,401		15,0	2,646	
	15,0	0,357		20,0	2,307	
22,0	6,0	0,803		25,0	2,005	
	8,0	0,759		28,0	1,749	
	10,0	0,702	30,0	1,557		
	12,0	0,631	45,0	15,0	3,397	
	14,0	0,546		20,0	3,118	
15,0	0,448	25,0		2,756		
16,0	0,453	30,0		2,308		
25,0	6,0	1,046		35,0	1,777	
	8,0	1,002	38,0	1,417		
	10,0	0,945	50,0	20,0	3,954	
	12,0	0,874		25,0	3,591	
	14,0	0,789		30,0	3,144	
	15,0	0,742		35,0	2,612	
	16,0	0,691		40,0	1,996	
	18,0	0,580		45,0	1,298	
20,0	0,540					

Rohre extrudiert

Durchmesser			Durchmesser			
D	d	Gewicht	D	d	Gewicht	
mm	mm	kg / m	mm	mm	kg / m	
55,0	20,0	4,874	90,0	50,0	11,026	
	25,0	4,511		60,0	9,245	
	30,0	4,064		65,0	8,226	
	35,0	3,532		68,0	7,574	
	40,0	2,916		75,0	5,932	
	45,0	2,216		80,0	4,657	
	48,0	1,755				
60,0	15,0	6,156	95,0	80,0	7,490	
	20,0	5,878	85,0	6,163		
	25,0	5,515	100,0	50,0	15,489	
	30,0	5,068		60,0	13,697	
	35,0	4,536		70,0	11,642	
	40,0	3,920		80,0	9,245	
	45,0	3,220		85,0	7,918	
	50,0	2,100		90,0	6,506	
55,0	1,567					
65,0	15,0	7,533		105,0	75,0	11,705
	20,0	7,370	85,0	9,759		
	25,0	7,045	90,0	8,364		
	30,0	6,635	98,0	5,908		
	35,0	6,140	110,0	75,0	14,253	
	40,0	5,565		80,0	13,012	
	45,0	4,950		90,0	10,273	
	50,0	4,155		95,0	8,523	
	55,0	3,325		100,0	7,191	
	60,0	2,140				
70,0	20,0	8,305	120,0	100,0	10,005	
	30,0	7,705	112,0	7,150		
	35,0	7,191	135,0	120,0	9,260	
	40,0	6,705		125,0	7,200	
	45,0	5,906		140,0	130,0	6,148
	50,0	5,300			125,0	16,479
	55,0	4,280	140,0		9,930	
	60,0	3,505				
80,0	25,0	10,966	160,0	150,0	7,076	
	30,0	10,546	205,0	195,0	9,106	
	35,0	10,041				
	40,0	9,451				
	50,0	8,012				
	55,0	7,165				
60,0	6,232					
	70,0	4,109				
	75,0	2,919				

Standard-Längen: 2000 mm

Toleranzen für die Längen: + 20 / - 0 mm

Toleranzen für die Durchmesser: D (mm) d (mm)

Außen-Durchmesser: bis 20 mm + 0,5 - 0,5
 bis 30 mm + 1,0 - 1,0
 bis 50 mm + 1,5 - 1,5
 bis 100 mm + 2,0 - 2,0
 bis 150 mm + 3,0 - 3,0
 über 150 mm + 5,0 - 5,0

Gewichte: ungefähre Gewichte der Effektivabmessungen